



excellence in panel products

ElecoFloor® - Floating Floor Treatments for concrete RSD separating floors

ElecoFloor® 23 and **ElecoFloor® 24** are resilient overlay shallow platform floor systems (Type FFT5) for use with Robust Standard Detail floor construction types MF1, MF8 and SF2.

ElecoFloor® 23 and **24** have been tested and are certified to provide the necessary acoustic insulation required for compliance with Part 'E' of the building regulations for these RSD floor types.

ElecoFloor® 23 panels comprise a resilient layer pre-bonded to 18mm T & G flooring grade chipboard.

ElecoFloor® 24 panels, at just 1mm thicker having a superior type resilient layer, will provide an additional 3 dB ΔL_w where a higher degree of sound insulation is desirable.

ElecoFloor® is available with or without strippable protective membrane.

Specification

Product	Size mm	Thickness mm	Density Kg/m ²	RSD compliance requirement dB ΔL_w	ElecoFloor® rating dB ΔL_w
ElecoFloor® 23	2400 x 600 TG4	23	13.20	17	18
ElecoFloor® 24	2400 x 600 TG4	24	14.18	17	21

Accessories

Joint adhesive, perimeter isolation and membrane jointing tapes are all available for use with **ElecoFloor®**

Availability

Please contact Stramit Industries Limited for details of supply.

Stramit Industries Limited is an ISO 9000 registered company.

Patents applied for.

Stramit Industries Limited, Oaksmere Business Park, Eye, Suffolk, IP23 8BW

w: eleco.com/stramit e: stramit@eleco.com t: +44 (0)1379 783465 f: +44 (0)1379 783659

