



SoundDead 19 Data Sheet

Introduction

SoundDead 19 has been designed for areas where greater Airborne noise reduction is required whilst still keeping floor height increase to a minimum, it is laid directly over this existing floor area with carpets and under lays fitted on top in the normal manner. It is specifically designed for reducing Airborne noise although it will also reduce impact noise transmission.

Benefits

Improves airborne sound Insulation. Approx 7-8dB**

Reduces impact Noise. Approx 15-20dB**

Simply laid under a Carpet and Underlay

Minimising increase in floor level.

Easily cut and shaped.

Easily and quickly installed.

Butts tight up to Perimeters.

Can allow access to existing floor.



Sheet Size 1m x 0.5m x 19mm

Material Composition

SoundDead 19 comes in a pre-laminated sheet composed of the following materials:

10kg/m² Polymeric Barrier Mat

10mm Thick Chip foam

10kg/m² Polymeric Barrier Mat

**In terms of precise Noise Reduction Figures it depends largely on what type of floor construction you are placing this material on, for accurate advice on whether this product is suitable or for a quote, please

call **0845 5212 096**

Please note, the success of any acoustic system, will depend entirely on the construction of the existing building and finishing detail, to the extent that we can not guarantee the level of noise reduction that will actually be achieved. It is the clients responsibility to check the quantities of materials ordered are correct as shortages will have to be paid for separately and to check with Local Building Control on possible testing requirements.